

Lexmark Color Laser Printers



				
	CS310dn	CS510de	CS720de	CS725de
Printing technology	Color Laser	Color Laser	Color Laser	Color Laser
Print speed (mono/color)	25/25 ppm	32/32 ppm	40/40 ppm	50/50 ppm
Time to first page	10.0 seconds	9.0 seconds	6.0 seconds	5.0 seconds
Print resolution	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi
Memory standard	256 MB	512 MB	1 GB	1 GB
Memory max	2.3 GB	2.56 GB	3 GB	3 GB
Processor	800 MHz Dual Core		Quad Core 1.2 GHz	
Hard disk	Not available		Option available (320 GB or more)	
Noise level, operating	48 dBA	50 dBA	51 dBA	53 dBA
Noise level, idle	16 dBA	16 dBA	15 dBA	15 dBA
Max monthly duty cycle	Up to 60,000 pages	Up to 85,000 pages	Up to 120,000 pages	Up to 150,000 pages
Recommended monthly volume	500 - 5,000 pages	1,500 - 7,000 pages	1,500 - 15,000 pages	2,000 - 20,000 pages
Supplies yield	K: 1,000/4,000 pages CMY: 1,000/3,000 pages Drum: 40,000 pages	K: 4,000/8,000 pages CMY: 1,000/3,000/4,000 pages Drum: 40,000 pages	CMYK: 3,000/7,000 pages K: 20,000 pages Drum: 150,000 pages	CMYK: 3,000/7,000 pages K: 20,000 pages CMY: 12,000 page Drum: 150,000 pages
Supplies/others	K: 1,400 pages (SWE) CMY: 1,400 pages (SWE)	K: 6,000 pages (SWE) CMY: 4,000 pages (SWE)	K: 3,000 pages (SWE) CMY: 3,000 pages (SWE)	K: 7,000 pages (SWE) CMY: 7,000 pages (SWE)
Standard paper handling	250 sheets	250 sheets	550-sheet tray with 100-Sheet Multipurpose Feeder	550-sheet tray with 100-Sheet Multipurpose Feeder
Paper handling options	550-sheet duo tray with 100-sheet feeder	550-sheet tray or 550-sheet duo tray with 100-sheet feeder	550-sheet tray	550-sheet tray
Maximum paper input	900 sheets	1,450 sheets	2,300 sheets	2,300 sheets
Paper output capacity	125 sheets	125 sheets	300 sheets	300 sheets
Standard ports	USB 2.0, Ethernet (10/100)	Front USB 2.0 (1 front/1 rear) Gigabit Ethernet (10/100/1000)	Front USB 2.0 (1 front/1 rear) Gigabit Ethernet (10/100/1000)	Front USB 2.0 (1 front/1 rear) Gigabit Ethernet (10/100/1000)



CS820de

C925de

C950de

Printing technology	Color Laser	Color LED	Color LED
Print speed (mono/color)	60/60 ppm	30/30 ppm	50/45 ppm
Time to first page	7.0 seconds	9.0 seconds	5.2 seconds
Print resolution	1200 x 1200 dpi	1200 x 1200 IQ	1200 x 1200 dpi
Memory standard	1 GB	256 MB	1.04 GB
Memory max	3 GB	1.28 GB	2.04 GB
Processor	Quad Core 1.33 GHz	800 MHz	1.2 GHz
Hard disk	Option available (320 GB or more)		
Noise level, operating	56 dBA	53 dBA	53 dBA
Noise level, idle	14 dBA	39 dBA	22 dBA
Max monthly duty cycle	Up to 200,000 pages	Up to 200,000 pages	Up to 225,000 pages
Recommended monthly volume	2,500 - 25,000 pages	2,500 - 10,000 pages	4,000 - 33,000 pages
Supplies yield	K: 33,000 pages CMY: 22,000 pages Drum: 175,000 pages	K: 8,500 pages CMY: 7,500 pages Drum: 30,000 pages	K: 32,000 pages CMY: 22,000 pages Drum: 115,000 pages
Supplies/others	K: 8,000 pages (SWE) CMY: 8,000 pages (SWE)	K: 8,500 pages (SWE) CMY: 7,500 pages (SWE)	K: 16,000 pages (SWE) CMY: 11,000 pages (SWE)
Standard paper handling	550-Sheet Input, 100-Sheet Multipurpose Feeder	150 + 250 + 50 sheets	520 + 100 sheets
Paper handling options	550-Sheet Tray, Inline Stapler, 2200-Sheet Tray	550-sheet tray	2,000-sheet high capacity feeder, 3 x 520-sheet trays stand, 2,520-sheet tandem tray module, 520-sheet tray stand + finisher
Maximum paper input	4,500 sheets	2,100 sheets	5,140 sheets
Paper output capacity	500 sheets	250 sheets	500 sheets
Standard ports	One internal Card Slot, USB 2.0 (1 front/2 rear), Gigabit Ethernet (10/100/1000)	USB 2.0 (1 front/1 rear), Gigabit Ethernet(10/100/1000)	USB 2.0 (1 front/1 rear), Gigabit Ethernet(10/100/1000)